

Overview

HP EliteBook 630 13.3 inch G9 Notebook PC



Left

- | | |
|--|--|
| 1. Internal Microphones (2) | 7. Smartcard Reader (Optional) |
| 2. Webcam LED (Optional) | 8. Audio Combo Jack |
| 3. Camera Shutter (Only available with webcam) | 9. SuperSpeed USB Type-A 5Gbps signaling rate port |
| 4. HD TNR and IR Camera (Optional) | 10. Ethernet Port (RJ-45) ¹ |
| 5. IR Camera LED (Optional) | 11. Nano Security Lock Slot (Lock sold separately) |
| 6. Clickpad | |

1. RJ-45 port icon may vary.

Overview



Right

1. Power Button Key
2. Power Connector
3. Thunderbolt™ 4 with USB4 Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)¹
4. SuperSpeed USB Type-A 5Gbps signaling rate port (Powered port) (USB 3.2 Gen 1)
5. HDMI 2.1 Port (Cable not included)
6. Touch Fingerprint Sensor (Select Models)

1. SuperSpeed USB 20Gbps is not available with Thunderbolt™ 4

Overview

AT A GLANCE

- Preinstalled with Windows 11 versions or FreeDOS
- Choice of 12th generation Intel® Core™ i7, i5 and i3 processors
- Fast and upgradeable dual channel DDR4 SODIMM memory up to 64 GB
- Choice of 33.8 cm (13.3") diagonal HD, Ultra Wide Viewing Angle FHD, Touch or Non-Touch screen, and Privacy Panel option
- Features redesigned quiet and responsive HP Keyboard with the HP Programmable key and backlit options
- Choice of solid state drives up to 1 TB
- Multi-layered security with HP SureStart Gen7¹, HP Privacy Camera, HP Sure View Gen4², HP Wolf Security (Includes HP Sure Sense³ and HP Sure Click⁴), HP Secure Erase⁵, HP Client Security Manager Gen7 (Includes Sure Run Gen5⁶, Sure Recover Gen5⁷), Touch Fingerprint reader⁸, and Tamper Lock⁹
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles¹⁰
- Designed to support HP docking options
- Passed MIL-STD 810G tests¹¹
- Battery life up to 11 hours 15 minutes
- Optimize your video calls with an HD camera and Temporal Noise Reduction that adjusts to the lighting in your environment.

1. HP Sure Start Gen7 is available on select HP PCs.

2. HP Sure View integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

3. HP Sure Sense is available on select HP PCs and is not available with Windows 11 Home.

4. HP Sure Click requires Windows 11. See https://bit.ly/2PrLT6A_SureClick for complete details.

5. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

6. HP Sure Run Gen4 is available on select Windows 11 based HP Pro, Elite and Workstation PCs with select Intel® or AMD processors.

7. HP Sure Recover Gen5 is available on select HP PCs and requires Windows 10 and higher and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module.

8. Sold separately or as an optional feature

9. HP Tamper Lock must be enabled by the customer or your administrator.

10. HP notebooks up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

11. MIL STD 810H testing is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Technical Specifications

PRODUCT NAME

HP EliteBook 630 13.3 inch G9 Notebook PC

OPERATING SYSTEM

Preinstalled Windows 11 Pro ¹
 Windows 11 Pro Education ¹
 Windows 11 Home – HP recommends Windows 11 Pro for Business ¹
 Windows 11 Home Single Language – HP recommends Windows 11 Pro for Business ¹
 Windows 11 Pro (Windows 11 Enterprise or Windows 10 Enterprise available with a Volume Licensing Agreement) ¹
 Windows 11 Pro (preinstalled with Windows 10 Pro Downgrade) ^{1,2}
 FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

PROCESSORS

Processor 3,4,5,6,7	Cores	Number of P-cores	Number of E-cores	Threads	L3 Cache	Max Turbo Frequency		Base Frequency		Intel SIPP/ vPro® Enterprise	Intel vPro® Essentials
						P-cores	E-cores	P-cores	E-cores		
Intel® Core™ i7-1265U	10	2	8	12	12MB	4.8 GHz	3.6 GHz	1.8 GHz	1.3 GHz	X	
Intel® Core™ i7-1255U	10	2	8	12	12MB	4.7 GHz	3.5 GHz	1.7 GHz	1.2 GHz		X
Intel® Core™ i5-1245U	10	2	8	12	12MB	4.4 GHz	3.3 GHz	1.2 GHz	1.2 GHz	X	
Intel® Core™ i5-1235U	10	2	8	12	12MB	4.4 GHz	3.3 GHz	1.3 GHz	0.9 GHz		X
Intel® Core™ i3-1215U	6	2	4	8	10MB	4.4 GHz	3.3 GHz	1.2 GHz	0.9 GHz		

Technical Specifications

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

7. Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

Intel® Iris® Xe Graphics (Core i5 and Core i7) ⁸

Intel® UHD Graphics (Core i3)

Supports

Support HD decode, DX12, HDMI 2.1b ⁹

8. Intel® Iris® Xe Graphics capabilities require system to be configured with Intel® Core™ i5 or i7 processors and dual channel memory. Intel® Iris® Xe Graphics with Intel® Core™ i5 or 7 processors and single channel memory will only function as UHD graphics.

9. HD content required to view HD images.

DISPLAY

Non-Touch

33.8 cm (13.3") diagonal, FHD (1920 x 1080), UWVA eDP 1.3+PSR, anti-glare, Low Blue Light, narrow bezel, 1000 nits, sRGB, 100% for HD + IR Camera, HP Sure View Reflect Gen4 integrated privacy screen with HP Eye Ease ^{9,11,12,13}

33.8 cm (13.3") diagonal, FHD (1920 x 1080), UWVA eDP 1.4+PSR2 anti-glare, LED, low power, narrow bezel, 400 nits, 72% for HD + IR Camera ^{9,11}

33.8 cm (13.3") diagonal, FHD (1920 x 1080), UWVA eDP 1.4+PSR2 anti-glare, LED, low power, narrow bezel, 400 nits, 72% for HD Camera ^{9,11}

33.8 cm (13.3") diagonal, FHD (1920 x 1080), UWVA eDP 1.2 w/o PSR, anti-glare, LED, narrow bezel, 250 nits, 45%, for HD + IR camera ^{9,11}

33.8 cm (13.3") diagonal, FHD (1920 x 1080), UWVA eDP 1.2 w/o PSR, anti-glare, LED, narrow bezel, 250 nits, 45%,

Technical Specifications

for HD camera ^{9,11}

33.8 cm (13.3") diagonal, HD (1366x768), SVA eDP, anti-glare, WLED, narrow bezel, 250 nits, 45% for HD camera ^{9,11}

33.8 cm (13.3") diagonal, HD (1366x768), SVA eDP, anti-glare, WLED, narrow bezel, 250 nits, 45% ^{9,11}

Touch

33.8 cm (13.3") diagonal, FHD (1920 x 1080), UWVA eDP 1.2 w/o PSR anti-glare, LED, narrow bezel, touch-on-panel screen, 250 nits, 45% for HD + IR camera ^{9,10,11,13}

33.8 cm (13.3") diagonal, FHD (1920 x 1080), UWVA eDP, anti-glare, LED, narrow bezel, touch-on-panel screen, 250 nits, 45%, for HD camera ^{9,10,11,13}

Display Size

13.3" diagonal

33.8 cm (13.3") diagonal

9. HD content required to view HD images.

10. Sold separately or as an optional feature.

11. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

12. HP Sure View Reflect integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

13. Actual brightness will be lower with touchscreen or HP Sure View.

DOCKING (Sold Separately)

Docking station model #1

HP USB-C Dock G5

Docking station model #2

HP USB-C/A Universal Dock G2

Docking station model #3

HP Thunderbolt Dock G2

Docking station model #4

HP TB Dock 120W w/Audio

Docking station model #5

HP TB Dock 230W w/Combo Cable

For additional aftermarket options and docking specs please see page 39.

STORAGE AND DRIVES

Primary M.2 Storage

1 TB PCIe® Gen4x4 NVMe™ M.2 TLC Solid State Drive ¹⁴

1 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC ^{14,15}

512 GB PCIe® Gen4x4 NVMe™ M.2 TLC Self Encrypted OPAL2 Solid State Drive ¹⁴

512 GB PCIe® Gen4x4 NVMe™ M.2 TLC Solid State Drive ¹⁴

512 GB PCIe® NVMe™ M.2 SSD ¹⁴

256 GB PCIe® Gen4x4 NVMe™ M.2 TLC Self Encrypted OPAL2 Solid State Drive ¹⁴

256 GB PCIe® Gen4x4 NVMe™ M.2 TLC single-sided Solid State Drive ¹⁴

256 GB PCIe® NVMe™ M.2 SSD ¹⁴

14. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

15. Available only to HK (Hong Kong), TW (Taiwan) and CN (China).

Technical Specifications

MEMORY

Maximum Memory

64 GB DDR4-3200 SDRAM ¹⁶

Memory

64 GB DDR4-3200 SDRAM (2x32GB) ¹⁶

32 GB DDR4-3200 SDRAM (2x16GB) ¹⁶

32 GB DDR4-3200 SDRAM (1x32GB) ¹⁶

16 GB DDR4-3200 SDRAM (2x8GB) ¹⁶

16 GB DDR4-3200 SDRAM (1x16GB) ¹⁶

8 GB DDR4-3200 SDRAM (1x8GB) ¹⁶

Memory Slots

2 SODIMM

Both slots are customer accessible / upgradeable

DDR4 PC4 SODIMMS (Alder Lake runs at 3200)

16. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

WLAN

Intel® AX211 Wi-Fi 6E +Bluetooth® 5.3 M.2 2230 160MHz CNVi WLAN Wireless Card ¹⁷

Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 M.2 2230 vPro 160MHz CNVi WLAN Wireless Card ¹⁷

NFC

NXP NPC300 Near Field Communication Module (NFC Mirage WNC XRAV-1)

Miracast

Native Miracast Support

Ethernet

Intel® I219-LM 1 Gigabit Network Connection LOM (vPro) ¹⁸

Intel® I219v 1 Gigabit Network Connection LOM (non-vPro) ¹⁸

Wake on WLAN

Support on S3 AC mode only

17. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

18. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

Technical Specifications

AUDIO/MULTIMEDIA

Audio

2 Integrated stereo speakers
Integrated microphone (Dual Array)

Speaker Power

2W/4ohm Per speaker

Camera

720p HD camera with Temporal Noise Reduction ⁹
720p HD camera+IR Camera with Temporal Noise Reduction ⁹

[9. HD content required to view HD images.](#)

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium Keyboard, spill resistant with optional backlit function ¹⁹

Pointing Device

Clickpad with multi-touch gesture support

Function Keys

F1 - Display Switching
F2 - Blank or SureView On/Off
F3 - Brightness Down
F4 - Brightness Up
F5 - Audio Mute
F6 - Volume Down
F7 - Volume Up
F8 - Mic Mute
F9 - Blank or Backlit Toggle
F10 - Insert
F11 - Wireless
F12 - Programmable key

Hidden Function Keys

Fn+R - Break
Fn+S - Sys Rq
Fn+C - Scroll Lock

[19. Backlit keyboard is an optional feature.](#)

Technical Specifications

SOFTWARE AND SECURITY

Software

HP Quick Touch

HP Quick Drop ²⁰

myHP

HP Smart Support ²¹

HP Connection Optimizer

HP Power Manager

HP Hotkey Support

HP Support Assistant ²²

HP Notifications

HP Privacy Settings

Buy Microsoft Office (Sold separately)

Manageability Features

HP Manageability Integration Kit Gen4 (download) ²³

HP Driver Packs (download)

HP Client Catalog (download)

HP Client Management Script Library (download)

HP Image Assistant (download)

NOTE: To enhance brightness, level go to the Intel® Graphics Command Center app, click on System and turn off the Display Power Savings function.

Security Management

HP Wolf Security for Business²⁴ includes:

HP Sure Click ²⁵

HP Sure Sense ²⁶

HP Sure Run Gen5 ²⁷

HP Sure Recover Gen5 ²⁸

HP Sure Start Gen7 ²⁹

HP Tamper Lock

HP Sure Admin ³⁰

HP Client Security Manager Gen7 ³¹

TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)

BIOS

HP BIOSphere Gen6 ³²

HP Secure Erase ³³

Absolute Persistence Module ³⁴

HP DriveLock & Automatic DriveLock

BIOS Update via Network

HP Wake on WLAN

HP Fingerprint Sensor ³⁵

Secured-Core PC Enable ³⁶

Security

TPM

Model: Infineon SLB9672VU2.0



Technical Specifications

Version: 15.21

Revision: TPM 2.0

FIPS 140-2 Compliant: Yes

Smartcard Reader

Model number: Alcor AU9560

FIPS 201 Compliant: Yes

IPv6 Support

Yes

FirstNet Certified

No

Is the BIOS on this notebook ISO/IEC 19678:2015 (formerly NIST 800-147) compliant?: Yes

UEFI version: 2.7

Class: 3

20. HP Quick Drop requires Internet access and Windows 10 or higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.
21. HP Smart Support automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights and is available preinstalled on select products, thru HP Factory Configuration Services; or it can be downloaded. For more information about how to enable HP Smart Support or for download, please visit <http://www.hp.com/smart-support>.
22. HP Support Assistant requires Windows and Internet Access.
23. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.
24. HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features and OS requirement.
25. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See https://bit.ly/2PrLT6A_SureClick for complete details.
26. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.
27. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.
28. HP Sure Recover Gen5 is available on select HP PCs and requires Windows 10 and higher and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module.
29. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher.
30. HP Sure Admin requires Windows 10 or higher, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.
31. HP Client Security Manager Gen7 requires Windows and is available on the select HP Elite and Pro PCs.
32. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
33. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
34. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>.
35. Fingerprint Reader is an optional feature that must be configured at purchase.

Technical Specifications

36. Requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.

POWER

Power Supply

HP Smart 65 W External AC power adapter ³⁷

HP Smart 65 W EM External AC power adapter ³⁷

HP Smart 65 W USB Type-C adapter ³⁷

HP Smart 45 W External AC power adapter ³⁷

HP Smart 45 W USB Type-C adapter ³⁷

Battery

HP Long Life 3-cell, 42.75 Wh Polymer ^{38,39}

Compliant with UL 1642 Standard

Power Cord

3-wire plug - 1m ³⁷

2-wire plug - 1m ³⁷

Battery life

Up to 11 hours 15 minutes with 42whr battery (HP Long Life 3-Cell, 42 Whr Polymer, UMA graphic, Intel U15, display set to 200 nits, 2*4G memory, 256 GB SSD) ⁴⁰

Battery Weight

HP Long Life 3-cell - 42.75 Wh Polymer - .40 lb

37. Availability may vary by country.

38. Battery is internal and not replaceable by customer. Serviceable by warranty.

39. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

40. Windows 10 MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

Technical Specifications

WEIGHTS & DIMENSIONS

Product Weight

Starting at 2.82 lb ⁴¹

Starting at 1.28 kg ⁴¹

Product Dimensions (W x D x H)

12.08 x 8.2 x 0.62 in

30.69 x 20.84 x 1.59 cm

41. Weight will vary by configuration. Does not include power adapter.

PORTS/SLOTS

1 Thunderbolt™ 4 with USB4™ Type-C® 40 Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) ⁴²

2 SuperSpeed USB Type-A 5Gbps signaling rate Port includes 1 Powered port (USB 3.2 Gen 1)

1 AC power

1 HDMI 2.1 ⁴³

1 Headphone/microphone combo jack

1 RJ-45 ⁴⁴

Expansion Slots

Smart Card Reader (optional)

42. SuperSpeed USB 20Gbps is not available with Thunderbolt™ 4

43. HDMI cable sold separately.

44. RJ-45 port icon may vary.

Technical Specifications

SERVICE AND SUPPORT

HP Services offers 1-year or 3-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.⁴⁵

45. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

CERTIFICATION AND COMPLIANCE

Energy Efficiency Compliance: ENERGY STAR® certified
Energy Efficiency Compliance: EPEAT® registered⁴⁶
Environmental Specifications: Low halogen⁴⁷
Environmental Specifications: TCO 9.0 Certification

46. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

47. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	19V
Average Operating Power	3.49W
Integrated graphics	Yes
Discrete Graphics	N/A
Max Operating Power	45W

Temperature

Operating	32° to 95° F (0° to 35° C) (No sustained direct exposure to sunlight) (System performance may be reduced above 32°C (89.6°F))
Non-operating	-4° to 140° F (-20° to 60° C)

Relative Humidity

Operating	10% to 90% (non-condensing)
Non-operating	5% to 95% (38.7° C (101.6° F) maximum wet bulb tempera-ture; non-condensing)

Shock

Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine

Random Vibration

Operating	1.043 grams
Non-operating	3.5 grams

Altitude (unpressurized)

Operating	10,000 ft (3,048 m)
Non-operating	40,000 ft (12,192 m)

Planned Industry Standard Certifications

Regulatory Model Number	HSN-Q33C
UL	Yes
CSA	Yes
FCC Compliance	Yes
ENERGY STAR®	Yes ⁴⁸
EPEAT®	EPEAT® Gold in the United States ⁴⁹
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes
UKRSERTCOMPUTER	Yes

Technical Specifications

48. All configurations of the HP Elitebook 630 G9 are Energy Star® certified and identified as HP Elitebook 630 G9 Energy Star on HP websites and on <http://www.energystar.gov>.

49. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

DISPLAYS

NOTE: All specifications represent the typical specifications provided by hp's component manufacturers; actual performance may vary either higher or lower.

1. Actual brightness will be lower with touchscreen or HP Sure View.

13.3 in FHD (1920 x 1080) Anti-Glare UWVA Low Blue Light sRGB NB2Y 1000 eDP 1.3+PSR 100 PrivacyG4 Plus flat LCD Panel	Outline Dimensions (W x H)	299.060 x 185.550 (max)
	Active Area	293.760 x 165.240 (typ)
	Weight	210 (max)
	Diagonal Size	13.3
	Thickness	2.2 / 3.9 (max)
	Interface	eDP 1.3
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	1500:1 (typ)
	Refresh Rate	60 Hz
	Brightness	1000 nits
	Pixel Resolution - Format	1920 x1080 (FHD)
	Backlight	WLED
	Pixel Resolution	RGB
	Color Gamut Coverage	sRGB 100%
	Color Depth	8
	Viewing Angle	UWVA 85/85/85/85
	Low Blue Light	Yes
	Power Consumption (W, EBL@ 150nits max/ 200nits max)	N/A

Panel LCD 13.3 inch FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR slim NWBZ	Outline Dimensions (W x H)	300.56 x 187.77 mm (max) (w/ PCB & w/o bracket)
	Active Area	293.76 x 165.24 mm (typ.)
	Weight	260 g (max)
	Diagonal Size	13.3 inch
	Thickness	3.0 mm (max)
	Interface	eDP 1.2 (2 lane)
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	600:1 (typ.)
	Refresh Rate	60 Hz
	Brightness	250 nits
	Pixel Resolution - Format	RGB Stripe
	Backlight	LED

Technical Specifications

Pixel Resolution	RGB Stripe
Color Gamut Coverage	45%
Color Depth	6 bits
Viewing Angle	UWVA 85/85/85/85
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.40 (max)/ NA

Panel LCD 13.3 inch FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP slim Touch on Panel NWBZ

Outline Dimensions (W x H)	300.56 x 187.77 mm (max)
Active Area	293.76 x 165.24 mm (typ.)
Weight	268 g (max)
Diagonal Size	13.3 inch
Thickness	3.2 mm (max)
Interface	eDP 1.2
Surface Treatment	Anti-Glare On-cell
Touch Enabled	Yes ¹
Contrast Ratio	600:1 (typ.)
Refresh Rate	60 Hz
Brightness	250 nits ¹
Pixel Resolution - Format	1920 x 1080 (FHD)
Backlight	LED
Pixel Resolution	RGB Stripe
Color Gamut Coverage	45%
Color Depth	6 bits
Viewing Angle	UWVA 85/85/85/85
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.70 (max)/ NA

Panel LCD 13.3 inch FHD (1920x1080) Anti-Glare WLED UWVA 72percent cg 400nits eDP 1.4+PSR2 ultraslim LP NWBZ

Outline Dimensions (W x H)	299.06 x 185.54 mm (max)
Active Area	293.76 x 165.24 mm (typ.)
Weight	170 g (max)
Diagonal Size	13.3 inch
Thickness	2.0 mm (max)
Interface	eDP 1.4 + PSR2 (2 lane)
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	1200:1 (typ.)
Refresh Rate	60 Hz
Brightness	400 nits
Pixel Resolution - Format	1920 x 1080 (FHD)
Backlight	LED

Technical Specifications

Pixel Resolution	RGB Stripe
Color Gamut Coverage	72%
Color Depth	8 bits
Viewing Angle	UWVA 85/85/85/85
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.09 (max)/ 1.30 (max)

Panel LCD 13.3-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP NWBZ ultraslim	Outline Dimensions (W x H)	300.56 x 187.77 mm (max) (w/ PCB & w/o bracket)
	Active Area	293.83 x 165.20 mm (typ.)
	Weight	260 g (max)
	Diagonal Size	13.3 inch
	Thickness	3.0 mm (max)
	Interface	eDP 1.2 (1 lane)
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	300:1 (typ.)
	Refresh Rate	60 Hz
	Brightness	250 nits
	Pixel Resolution - Format	1366 x 768 (HD)
	Backlight	LED
	Pixel Resolution	RGB Stripe
	Color Gamut Coverage	NTSC 45%
	Color Depth	6 bits
	Viewing Angle	SVA 45/45/15/35
Low Blue Light	No	
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.95 (max) / 2.37 (max)	

Technical Specifications

STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

SSD 256GB 2280 PCIe-4x4 NVMe Three Layer Cell	Drive Weight	M.2 2280
	Rotation speed	256 GB
	Cache Buffer	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	0.02 lb (10 g)
	Transfer Rate	PCIe NVMe Gen4
	Seek Time	Up to 6,400 MB/s
	Logical Blocks	Up to 2,700 MB/s
	Operating Temperature	500,118,192
	Security Features	32° to 158°F (0° to 70°C) [ambient temp]
	Features	Pyrite 2.0; TRIM; L1.2

256GB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive	Drive Weight	M.2 2280
	Rotation speed	256GB
	Cache Buffer	TLC
	NAND Type/Size	NA
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	0.02 lb (10 g)
	Transfer Rate	PCIe NVMe Gen4
	Seek Time	6400
	Logical Blocks	2700
	Operating Temperature	500,118,192
	Security Features	32° to 158°F (0° to 70°C) [ambient temp]
Features	ATA Security (Option); TCG Opal 2.0; TRIM; L1.2	

SSD 512GB 2280 PCIe NVMe Value	Drive Weight	M.2 2280
	Rotation speed	512GB
	Cache Buffer	Value
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	0.02 lb (10 g)
	Transfer Rate	PCIe NVMe Gen3
	Seek Time	Up to 3500 MB/s
	Logical Blocks	up to 3000 MB/s
	Operating Temperature	1,000,215,216
	Security Features	32° to 158°F (0° to 70°C) [ambient temp]
	Features	TRIM; L1.2

Technical Specifications

SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell	Drive Weight	M.2 2280
	Rotation speed	512GB
	Cache Buffer	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	0.02 lb (10 g)
	Transfer Rate	PCIe NVMe Gen4
	Seek Time	Up to 6,600 MB/s
	Logical Blocks	Up to 5,100 MB/s
	Operating Temperature	1,000,215,216
	Security Features	32° to 158°F (0° to 70°C) [ambient temp]
	Features	Pyrite 2.0; TRIM; L1.2

512GB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive	Form Factor	M.2 2280
	Capacity	512GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (10 g)
	Interface	PCIe NVMe Gen4
	Maximum Sequential Read	Up to 6,600 MB/s
	Maximum Sequential Write	Up to 5,100 MB/s
	Logical Blocks	1,000,215,216
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	ATA Security (Option); TCG Opal 2.0; TRIM; L1.2

SSD 1TB 2280 PCIe-4x4 NVMe Three Layer Cell	Form Factor	M.2 2280
	Capacity	1TB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (10 g)
	Interface	PCIe NVMe Gen4
	Maximum Sequential Read	Up to 7,100 MB/s
	Maximum Sequential Write	Up to 5,200 MB/s
	Logical Blocks	2,000,409,264
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	Pyrite 2.0; TRIM; L1.2

Technical Specifications

SSD 1 TB 2280 PCIe NVMe Value¹	Form Factor	M.2 2280
	Capacity	1TB
	NAND Type	TLC
	Interface	PCIe NVMe Gen4X4
	Maximum Sequential Read	Up to 3200 MB/s \pm 20%
	Maximum Sequential Write	Up to 2700 MB/s \pm 20%
	Logical Blocks	2,000,409,264
	Features	Pyrite 2.0; TRIM; L1.2

1. Available only to HK (Hong Kong), TW (Taiwan) and CN (China).

Technical Specifications

NETWORKING/COMMUNICATIONS

<p>Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card M.2 160MHz CNVi WW WLAN vPro¹</p>	<p>Wireless LAN Standards</p>	<ul style="list-style-type: none"> IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	<p>Interoperability</p>	<ul style="list-style-type: none"> Wi-Fi certified
	<p>Frequency Band</p>	<ul style="list-style-type: none"> •802.11b/g/n/ax 2.402 – 2.482 GHz •802.11a/n/ac/ax 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz 5.955 – 6.415 GHz 6.435 – 6.515 GHz 6.535 – 6.875 GHz 6.895 – 7.115 GHz
	<p>Data Rates</p>	<ul style="list-style-type: none"> •802.11b: 1, 2, 5.5, 11 Mbps •802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: max 300Mbps •802.11ac : 1733Mbps • 802.11ax : max 2.4Gbps
	<p>Modulation</p>	<ul style="list-style-type: none"> Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	<p>Security³</p>	<ul style="list-style-type: none"> •IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only •AES-CCMP: 128 bit in hardware •802.1x authentication •WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. •WPA2 certification •WPA3 certification •IEEE 802.11i •WAPI
	<p>Network Architecture Models</p>	<ul style="list-style-type: none"> Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<p>Roaming</p>	<ul style="list-style-type: none"> IEEE 802.11 compliant roaming between access points
	<p>Output Power²</p>	<ul style="list-style-type: none"> • 802.11b : +17dBm minimum

Technical Specifications

	<ul style="list-style-type: none"> • 802.11g : +16dBm minimum • 802.11a : +17dBm minimum • 802.11n HT20(2.4GHz) : +14dBm minimum • 802.11n HT40(2.4GHz) : +13dBm minimum • 802.11n HT20(5GHz) : +14dBm minimum • 802.11n HT40(5GHz) : +13dBm minimum • 802.11ac VHT80(5GHz) : +10dBm minimum • 802.11ac VHT160(5GHz) : +10dBm minimum • 802.11ax HE40(2.4GHz) : +12dBm minimum • 802.11ax HE80(5GHz) : +10dBm minimum • 802.11ax HE160(5GHz) : +10dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode 2.0 W • Receive mode 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode 50 mW (WLAN unassociated) • Connected Standby 10 mW • Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	<ul style="list-style-type: none"> • 802.11b, 1Mbps : -93.5dBm maximum • 802.11b, 11Mbps : -84dBm maximum • 802.11a/g, 6Mbps : -86dBm maximum • 802.11a/g, 54Mbps : -72dBm maximum • 802.11n, MCS07 : -67dBm maximum • 802.11n, MCS15 : -64dBm maximum • 802.11ac, MCS0(VHT80) : -84dBm maximum • 802.11ac, MCS9(VHT80) : -59dBm maximum • 802.11ac, MCS9(VHT160) : -58.5dBm maximum • 802.11ax, MCS11(HE40) : -57dBm maximum • 802.11ax, MCS11(HE80) : -54dBm maximum • 802.11ax, MCS11(HE160) : -53.5dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	<ol style="list-style-type: none"> 1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	<ol style="list-style-type: none"> 1. Type 2230: 2.8g 2. Type 1216: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m)

Technical Specifications

Non-operating 0 to 50,000 ft (15,240 m)

LED Activity

LED Amber – Radio OFF

LED OFF – Radio ON

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card

Bluetooth Specification

4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant

Frequency Band

2402 to 2480 MHz

Number of Available Channels

Legacy: 0~79 (1 MHz/CH)

BLE: 0~39 (2 MHz/CH)

Data Rates and Throughput

Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps

BLE: 1 Mbps data rate; throughput up to 0.2 Mbps

Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Transmit Power

The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Technical Specifications

<p>Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card M.2 160MHz CNVi WLAN non-vPro¹</p>	<p>Wireless LAN Standards</p>	<ul style="list-style-type: none"> IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	<p>Interoperability</p>	<ul style="list-style-type: none"> Wi-Fi certified
	<p>Frequency Band</p>	<ul style="list-style-type: none"> •802.11b/g/n/ax 2.402 – 2.482 GHz •802.11a/n/ac/ax 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz 5.955 – 6.415 GHz 6.435 – 6.515 GHz 6.535 – 6.875 GHz 6.895 – 7.115 GHz
	<p>Data Rates</p>	<ul style="list-style-type: none"> •802.11b: 1, 2, 5.5, 11 Mbps •802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: max 300Mbps •802.11ac : 1733Mbps •802.11ax : max 2.4Gbps
	<p>Modulation</p>	<ul style="list-style-type: none"> Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	<p>Security³</p>	<ul style="list-style-type: none"> •IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only •AES-CCMP: 128 bit in hardware •802.1x authentication •WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. •WPA2 certification •WPA3 certification •IEEE 802.11i •WAPI
	<p>Network Architecture Models</p>	<ul style="list-style-type: none"> Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<p>Roaming</p>	<ul style="list-style-type: none"> IEEE 802.11 compliant roaming between access points
	<p>Output Power²</p>	<ul style="list-style-type: none"> • 802.11b : +17dBm minimum • 802.11g : +16dBm minimum

Technical Specifications

	<ul style="list-style-type: none"> • 802.11a : +17dBm minimum • 802.11n HT20(2.4GHz) : +14dBm minimum • 802.11n HT40(2.4GHz) : +13dBm minimum • 802.11n HT20(5GHz) : +14dBm minimum • 802.11n HT40(5GHz) : +13dBm minimum • 802.11ac VHT80(5GHz) : +10dBm minimum • 802.11ac VHT160(5GHz) : +10dBm minimum • 802.11ax HE40(2.4GHz) : +12dBm minimum • 802.11ax HE80(5GHz) : +10dBm minimum • 802.11ax HE160(5GHz) : +10dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode 2.0 W • Receive mode 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode 50 mW (WLAN unassociated) • Connected Standby 10mW • Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	<ul style="list-style-type: none"> • 802.11b, 1Mbps : -93.5dBm maximum • 802.11b, 11Mbps : -84dBm maximum • 802.11a/g, 6Mbps : -86dBm maximum • 802.11a/g, 54Mbps : -72dBm maximum • 802.11n, MCS07 : -67dBm maximum • 802.11n, MCS15 : -64dBm maximum • 802.11ac, MCS0(VHT80) : -84dBm maximum • 802.11ac, MCS9(VHT80) : -59dBm maximum • 802.11ac, MCS9(VHT160) : -58.5dBm maximum • 802.11ax, MCS11(HE40) : -57dBm maximum • 802.11ax, MCS11(HE80) : -54dBm maximum • 802.11ax, MCS11(HE160) : -53.5dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	<ol style="list-style-type: none"> 1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	<ol style="list-style-type: none"> 1. Type 2230: 2.8g 2. Type 1216: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	<p>Operating 14° to 158° F (-10° to 70° C)</p> <p>Non-operating -40° to 176° F (-40° to 80° C)</p>
Humidity	<p>Operating 10% to 90% (non-condensing)</p> <p>Non-operating 5% to 95% (non-condensing)</p>
Altitude	<p>Operating 0 to 10,000 ft (3,048 m)</p> <p>Non-operating 0 to 50,000 ft (15,240 m)</p>

Technical Specifications

LED Activity LED Amber – Radio OFF;
LED Off – Radio ON

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card

Bluetooth Specification 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant

Frequency Band 2402 to 2480 MHz

Number of Available Channels Legacy: 0~79 (1 MHz/CH)
BLE: 0~39 (2 MHz/CH)

Data Rates and Throughput Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps
BLE: 1 Mbps data rate; throughput up to 0.2 Mbps
Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Transmit Power The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. 1. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Near Field Communications Controller (optional)	Dimensions (L x W x H)	Module 17 mm by 10 mm by 2.0 mm
	Chipset	NPC300
	System interface	I2C
	NFC RF standards	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
	NFC Forum Support Reader (PCD-VCD) Mode(1)	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2 ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz cards
	Card Emulation (PICC-VICC) Mode(1)	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
	Frequency	13.56 MHz

Technical Specifications

NFC Modes Supported	Reader/Writer, Peer-to-Peer
Raw RF Data Rates	106, 212, 424, 848 kbps
Operating temperature	0°C to 70°C
Storage temperature	-20°C to 125°C
Humidity	10-90% operating 5-95% non-operating
Supply Operating voltage	2.97 to 5.5 Volts
I/O Voltage	1.8V or 3.3V
Dimensions (L x W x H)	Module 17 mm by 10 mm by 2.0 mm

Power Consumption

(Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)

Mode	Power Consumption, Typical
Polling	7.3 mA
Detected Test Tag Type 1	32.9 mA
Detected Test Tag Type 2	70.7 mA
Detected Test Tag Type 3	79.2 mA
Detected Test Tag Type 4	64.9 mA

Antenna Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.

Intel® I219-LM 1 Gigabit Network Connection LOM (vPro)

Ethernet Features	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
Power Management	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
Performance Features	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling(Hash Mode Only) Jumbo Frame 9K
Manageability	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
Interface	PCI(Intel proprietary) + SMBus
NIC Device Driver Name	Intel(R) Ethernet Connection (13) I219-LM

Technical Specifications

<p>Intel® I219v 1 Gigabit Network Connection LOM (non-vPro)</p>	<p>Ethernet Features</p>	<ol style="list-style-type: none"> 1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) 4. Auto-Negotiation (Automatic Speed Selection) <p>Full Duplex Operation at all Speeds, Half Duplex operation at 10, 100 & 1000 Mbit/s</p>
	<p>Power Management</p>	<p>ACPI compliant – multiple power modes</p> <p>Situation-sensitive features reduce power consumption</p> <p>Advanced link down power saving for reducing link down power consumption</p>
	<p>Performance Features</p>	<p>TCP/IP/UDP Checksum Offload (configurable)</p> <p>Protocol Offload (ARP & NS)</p> <p>Large send offload and Giant send offload</p> <p>Receiving Side Scaling (Hash Mode only)</p> <p>Jumbo Frame 9K</p>
	<p>Manageability</p>	<p>Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)</p> <p>PXE 2.1 Remote Boot</p> <p>Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))</p> <p>Comprehensive diagnostic and configuration software suite</p> <p>Virtual Cable Doctor for Ethernet cable status</p>
	<p>Interface</p> <p>NIC Device Driver Name</p>	<p>PCI (Intel proprietary) + SMBus</p> <p>Intel(R) Ethernet Connection I219-V</p>

Technical Specifications

POWER

AC Adapter 45 Watt nPFC Standard USB type C Straight 1.8m	Dimensions	94.0 mm x 40.0 mm x 26.5 mm
	Weight	192.5g +/-10%
	Input	100~240 VAC
	Input Efficiency	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V: 81.5% 9V: 86.7% 12V: 87.41% 15V: 87.8%
	Input frequency range	47 to 63 Hz
	Input AC current	Max. 1.4 A at 90 Vac
	Output	
	Output power	5V/15W 9V/27W 12V/36W 15V/45W
	DC output	5V/9V/12V/15V
	Hold-up time	5ms at 115 Vac input
	Output current limit	<5.0A
	Connector	USB Type-C
	Environmental Design	
	Operating temperature	32° to 95° F (0° to 35° C)
	Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
	EMI and Safety	Eg.
	Certifications	*CE Mark - full compliance with LVD and EMC directives *Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. *MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m	Dimensions	95 x 45 x 26.5 mm
	Weight	unit: 200g +/- 10g
	Input	100~240 VAC
	Input Efficiency	87.74 % at 115 Vac and 88.4 % at 230Vac
	Input frequency range	47 ~ 63 Hz
	Input AC current	Max. 1.4 A at 90 Vac
	Output	
	Output power	45W
	DC output	19.5V
	Hold-up time	5ms at 115 Vac input

Technical Specifications

Output current limit	<8.0A
Connector	4.5mm Barrel Type
Environmental Design	
Operating temperature	32° to 95° F (0° to 35° C)
Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
Altitude	0 to 16,400 ft (0 to 5000m)
Humidity	20% to 95%
Storage Humidity	10% to 95%
EMI and Safety Certifications	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 65 Watt nPFC Standard USB type C Straight 1.8m	Dimensions	90.0 x 51 x 28.5mm
	Weight	unit: 250g +/- 10g
	Input	100~240 VAC
	Input Efficiency	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V: 81.5% 9V: 86.7% 12V: 88% 15V: 88% 20V: 89%
	Input frequency range	47 ~ 63Hz
	Input AC current	1.6 A at 90 VAC and maximum load
	Output	
	Output power	5V/15W 9V/27W 12V/60W 15V/60W 20V/65W
	DC output	5V/9V/12V/15V/20V
	Hold-up time	5ms at 115 Vac input
	Output current limit	<8.0A
	Connector	USB Type-C
	Environmental Design	
	Operating temperature	32° to 95° F (0° to 35° C)
	Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
Altitude	0 to 16,400 ft (0 to 5000m)	
Humidity	20% to 95%	

Technical Specifications

Storage Humidity	10% to 95%
EMI and Safety Certifications	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm New EM	Dimensions	102 x 55 x 30mm
	Weight	unit: 250g +/- 10g
	Input	100~240 VAC
	Input Efficiency	88.0 % at 115 Vac and 89.0 % at 230Vac
	Input frequency range	47 ~ 63 Hz
	Input AC current	Max. 1.7 A at 90 Vac
	Output	
	Output power	65W
	DC output	19.5V
	Hold-up time	5ms at 115 Vac input
	Output current limit	<11.0A
	Connector	4.5mm Barrel Type
	Environmental Design	
	Operating temperature	32°F to 95°F (0°to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
Storage Humidity	10% to 95%	
EMI and Safety Certifications	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.	

Technical Specifications

<p>AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m</p>	<p>Dimensions Weight Input Input Efficiency Input frequency range Input AC current Output Output power DC output Hold-up time Output current limit Connector Environmental Design Operating temperature Non-operating (storage) temperature Altitude Humidity Storage Humidity EMI and Safety Certifications</p>	<p>90 x 51 x 28.5mm Unit: 230g +/-10% 100~240 VAC 88.0 % at 115 Vac and 89.0 % at 230 Vac 47 ~ 63 Hz Max. 1.7 A at 90 Vac 65W 19.5V 5 ms at 115 Vac input <11.0A 4.5mm Barrel Type 32°F to 95°F (0°to 35°C) -4°F to 185°F (-20°to 85°C) 0 to 16,400 ft (0 to 5000m) 20% to 95% 10% to 95% Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.</p>
--	--	---

<p>AC Adapter 65 Watt nPFC Slim USB type C Straight 1.8m</p>	<p>Dimensions Weight Input Input Efficiency Input frequency range Input AC current Output Output power DC output Hold-up time Output current limit Connector Environmental Design</p>	<p>88 x 53.5 x 21 mm unit: 220g +/- 10g 100~240 VAC 81.5% min at 115 Vac/ 230Vac @ 5V/3A 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 15V/4.33A 89% min at 115 Vac/ 230Vac @ 20V/3.25A 47 ~ 63 Hz 1.7 A at 90 VAC and maximum load 65W 5V/9V/12V/15V/20V 5ms at 115 Vac input <8.0A USB Type C</p>
---	---	--

Technical Specifications

Operating temperature	32°F to 95°F (0° to 35°C)
Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
Altitude	0 to 16,400 ft (0 to 5000m)
Humidity	5% to 95%
Storage Humidity	5% to 95%
EMI and Safety Certifications	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

RH 42Whr¹ Long Life Polymer Fast Charge² 3 cell Battery	Dimensions (H x W x L)	6.2 x 76.25 x 249.50 mm (0.244 x 3.002 x 9.823 inch)
	Weight	0.18 kg (0.397 lb)
	Cells/Type	3cell Lithium-Ion Polymer cell / 545974
	Energy	
	Voltage	11.4V
	Amp-hour capacity	3.752Ah
	Watt-hour capacity	42.75Wh
	Temperature	
	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 122° F (-10° to 60° C)
	Fuel Gauge LED	NA
	Warranty	Follow Product Spec.
	Optional Travel Battery Available	No

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.
2. Recharges your battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

Technical Specifications

AUDIO

HD Stereo Codec	Realtek ALC3247-CG
Audio I/O Ports	Headset: CTIA only and Headphone-out
Internal Speaker Amplifier	ALC 3247 has Embedded Class-D 2W Stereo Amplifier
Multi-streaming Capable	Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behavior
Sampling	DAC:44.1k/48kHz ADC:48kHz
Wavetable Syntheses	NA
Analog Audio	Support 3.5mm Headset: CTIA only and Headphone-out
# of Channels on Line-Out	NA
Internal Speaker	Yes

FINGERPRINT READER

Sensor vendor	Elan efsa80ST
Sensor type	Capacitive
DPI resolution	508 dpi
Scan area	80*80 pixels
False Rejection Rate	<3%
False Acceptance Rate	1/100K
Mobile Voltage Operation	2.7V to 3.6V
Operating Temperature	-4 – 175°F (-20° ~ +80°C)
Current Consumption	
Image	50mA peak
Low Latency Wait For Finger	900uA
Capture Rate	30 frame/sec
ESD Resistance	+15KV
Detection Matrix	80*80 pixels/ 508 dpi / 4*4mm sensor area

Technical Specifications

ENVIRONMENTAL DATA

Eco-Label Certifications & declarations	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> • IT ECO declaration • US ENERGY STAR® • US Federal Energy Management Program (FEMP) • EPEAT[®] Gold registered in the United States. See http://www.epeat.net for registration status in your country. • TCO Certified • China Energy Conservation Program (CECP) • China State Environmental Protection Administration (SEPA) • Taiwan Green Mark • Korea Eco-label • Japan PC Green label* 		
Sustainable Impact Specifications	<ul style="list-style-type: none"> • Ocean-bound plastic in Speaker • 10% post-consumer recycled plastic • Low halogen • Outside Box and corrugated cushions are 100% sustainably sourced and recyclable • Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable • Bulk packaging available 		
System Configuration	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.</p>		
Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Sort idle)	5.06 W	5.29 W	5.34 W
Normal Operation (Long idle)	0.95 W	1.03 W	0.93 W
Sleep	0.95 W	1.03 W	0.93 W
Off	0.28 W	0.31 W	0.28 W
	<p>NOTE: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Short idle)	17.3 BTU/hr	18.1 BTU/hr	17.3 BTU/hr
Normal Operation (Long idle)	3.2 BTU/hr	3.5 BTU/hr	3.2 BTU/hr
Sleep	3.2 BTU/hr	4.7 BTU/hr	3.2 BTU/hr

Technical Specifications

Off	1 BTU/hr	1.1 BTU/hr	1 BTU/hr
	*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.		
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L _{WAd} , bels)	Sound Pressure (L _{pAm} , decibels)	
Typically Configured – Idle	2.6	13.2	
Fixed Disk – Random writes	3.5	32.7	
Optical Drive – Sequential reads	3.5	32.7	
Longevity and Upgrading	This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the		
	Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.		
Additional Information	<ul style="list-style-type: none"> • This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC. • This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC. • This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). • This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net • Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043. • This product is 92,8% recycle-able when properly disposed of at end of life. 		
Packaging Materials	External:	PAPER/Corrugated	281 g
		PAPER/Molded Pulp	144 g
	Internal:	PLASTIC/Polyethylene low density - LDPE	9 g
		The plastic packaging material contains at least 0.0% recycled content.	
		The corrugated paper packaging materials contains at least 53.1% recycled content.	
RoHS Compliance	<p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.</p>		

Technical Specifications

	<p>To obtain a copy of the HP RoHS Compliance Statement, see Error! Referencia de hipervínculo no válida. HP RoHS position statement.</p>
<p>Material Usage</p>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):</p> <ul style="list-style-type: none"> • Asbestos • Certain Azo Colorants • Certain Brominated Flame Retardants – may not be used as flame retardants in plastics • Cadmium • Chlorinated Hydrocarbons • Chlorinated Paraffins • Bis(2-Ethylhexyl) phthalate (DEHP) • Benzyl butyl phthalate (BBP) • Dibutyl phthalate (DBP) • Diisobutyl phthalate (DIBP) • Formaldehyde • Halogenated Diphenyl Methanes • Lead carbonates and sulfates • Lead and Lead compounds • Mercuric Oxide Batteries • Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. • Ozone Depleting Substances • Polybrominated Biphenyls (PBBs) • Polybrominated Biphenyl Ethers (PBBEs) • Polybrominated Biphenyl Oxides (PBBOs) • Polychlorinated Biphenyl (PCB) • Polychlorinated Terphenyls (PCT) • Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. • Radioactive Substances • Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
<p>Packaging Usage</p>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> • Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. • Eliminate the use of ozone-depleting substances (ODS) in packaging materials. • Design packaging materials for ease of disassembly. • Maximize the use of post-consumer recycled content materials in packaging materials. • Use readily recyclable packaging materials such as paper and corrugated materials. • Reduce size and weight of packages to improve transportation fuel efficiency. • Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

Technical Specifications

End-of-life Management and Recycling	<p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
HP, Inc. Corporate Environmental Information	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</p> <p>Eco-label certifications http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</p> <p>ISO 14001 certificates: http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842 and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</p>
footnotes	<ul style="list-style-type: none"> • Percentage of ocean-bound plastic contained in each component varies by product • Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard. • External power supplies, WWAN modules, power cords, cables and peripherals excluded. • 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers. • Fiber cushions made from 100% recycled wood fiber and organic materials.

COUNTRY OF ORIGIN

China

Options and Accessories (sold separately and availability may vary by country)

DOCKING (Sold Separately)

Docking station model #1	HP USB-C Dock G5
Total number of supported displays (incl. the notebook display)	3
Max. resolutions supported	Dual 5K@ 30Hz + 1 4K UHD (multi-function mode) 5120x2880
Dock Connectors	1xHDMI, 2xDP
Technical limitations	<p>Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode.</p> <p>Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode</p> <p>The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.</p>
Docking station model #2	HP USB-C/A Universal Dock G2
Total number of supported displays (incl. the notebook display)	3
Max. resolutions supported	Triple 4K UHD@ 60Hz 3840x2160
Dock Connectors	1xHDMI, 2xDP
Technical limitations	<p>The best resolution for dual or triple displays is 4K UHD@ 60Hz.</p> <p>For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from the host</p>
Docking station model #3	HP Thunderbolt Dock G2
Total number of supported displays (incl. the notebook display)	4
Max. resolutions supported	<p>Dual 4K @30Hz or dual 4K UHD @ 60Hz is supported</p> <p>Dual 8K@ 60Hz for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode</p>
Dock Connectors	2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode
Technical limitations	<p>Thunderbolt Hosts:</p> <p>Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.</p> <p>Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz</p> <p>Non-Thunderbolt hosts:</p> <p>The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is</p> <p>(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port</p> <p>Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.</p>
Docking station model #4	HP TB Dock 120W w/Audio
Total number of supported displays (incl. the notebook display)	4

Options and Accessories (sold separately and availability may vary by country)

Max. resolutions supported

Dual 4K @30Hz or dual 4K UHD @ 60Hz is supported
 Dual 8K@ 60Hz for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode
 2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode

Dock Connectors

Technical limitations

Thunderbolt Hosts:
 Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.
 Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz
 Non-Thunderbolt hosts:
 The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is
 (1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port
 Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

Docking station model #5

Total number of supported displays (incl. the notebook display)

Max. resolutions supported

HP TB Dock 230W w/Combo Cable

4

Dock Connectors

Technical limitations

Dual 4K @30Hz or dual 4K UHD @ 60Hz is supported
 Dual 8K@ 60Hz for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode
 2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode
 Thunderbolt Hosts:
 Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.
 Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz
 Non-Thunderbolt hosts:
 The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is
 (1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port
 Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

Options and Accessories (sold separately and availability may vary by country)

Category	Description	Part Number
Audio/Video	HP Wired USB-A Stereo Headset	428K6AA
	HP Wired 3.5mm Stereo Headset	428K7AA
Cases	HP Business 14.1 Sleeve	2UW01AA
	HP Business Slim 17.3 Top Load	2UW02AA
	HP Executive 14.1 Tote	6KD10AA
	HP Executive 15.6 Backpack	6KD07AA
	HP Executive 15.6 Top Load	6KD06AA
	HP Executive 17.3 Backpack	6KD05AA
	HP Executive 17.3 Top Load	6KD08AA
	HP Executive Leather 15.6 Top Load	6KD09AA
	HP Executive Slim 14.1 Top Load	6KD04AA
	HP Prelude G2 15.6 Backpack	1E7D6AA
	HP Prelude G2 15.6 Top Load	1E7D7AA
	HP Prelude Pro Recycled 15.6 Backpack	1X644AA
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA
	HP Renew 14 Laptop Sleeve	2E6U9AA,2E6V0AA
	HP Renew Business 14.1 Laptop Sleeve	3E2U7AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Business 14.1 Laptop Bag	3E5F9AA
HP Renew Business 15.6 Laptop Bag	3E5F8AA	
HP Reversible 13.3 Sleeve	7ZE82A6	
Docking	HP USB-C Dock G5	5TW10AA
	HP USB-C/A Universal Dock G2	5TW13AA
	HP Thunderbolt Dock 120W G2	2UK27AA
	HP TB Dock 120W w/Audio	3YE87AA
	HP TB Dock w/Combo Cable (230W)	3TR87AA
	HP Thunderbolt Dock 120W G4	4J0A2AA
	HP Thunderbolt 280W Dock G4 w/Combo Cable	4J0G4AA
Hub	HP USB-C Mini Dock	1PM64AA
	HP Universal USB-C Multiport Hub	50H55AA
	HP USB-C Travel Dock G2	7PJ38AA
	HP USB-C to USB-A Hub	Z6A00AA
Adapter	HP HDMI to DVI Adapter	F5A28AA
	HP HDMI to VGA Adapter	H4F02AA
	HP USB-C to DisplayPort Adapter	N9K78AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to USB 3.0 Adapter	N2Z63AA
	HP USB-C to VGA Adapter	N9K76AA

Options and Accessories (sold separately and availability may vary by country)

Keyboard/Combo	HP 975 USB+BT Dual-Mode Wireless Keyboard	3Z726AA
	HP 455 Programmable Wireless Keyboard	4R177AA
	HP 125 WD USB Keyboard	266C9AA
	HP 320K WD USB Keyboard	9SR37AA
	HP 655 Wireless Keyboard and Mouse Combo	4R009AA
	HP 225 Wired Mouse and Keyboard Combo	286J4AA
	HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA
	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
HP Wireless Rechargeable 950MK Mouse and Keyboard	3M165AA	
Mouse	HP USB Premium Wireless Mouse	1JR31AA
	HP 435 Multi-Device Wireless Mouse	3B4Q5AA
	HP 125 USB-A Wired Mouse	265A9AA
	HP 128 USB Laser Wired Mouse	265D9AA
	HP 320M USB-A Wired Mouse	9VA80AA
	HP Creator USB-A+Bluetooth 935 Wireless Mouse Black	1D0K8AA
	HP USB-A+Bluetooth Multi-Device 635 Wireless Mouse Black	1D0K2AA
	HP USB-A+Bluetooth Travel Bluetooth Mouse	6SP30AA
Power	HP 65W USB-C Auto Chevy AC Power Adapter	5TQ76AA
	HP 45W 4.5 mm Smart AC Power Adapter	H6Y88AA
	HP 45W USB-C G2 Zeus AC Power Adapter	1HE07AA
	HP 45W USB-C LC Dali AC Power Adapter	1MZ01AA
	HP 65W 4.5 mm LC Smart non-EM India Only AC Power Adapter	3FF84AA#ACJ
	HP 65W 4.5 mm Smart AC Power Adapter	H6Y89AA
	HP 65W 4.5 mm wDongle 7.4 mm Slim AC Power Adapter	H6Y82AA
	HP 65W USB-C Hades AC Power Adapter	1HE08AA
Commodity	HP USB DVD-Writer EXT ODD	F2B56AA
	HP Nano Keyed Cable Lock	1AJ39AA
	HP Nano Master Keyed Cable Lock	1AJ40AA
	HP SureKey Standard/Nano/Wedge Cable Lock	6UW42AA

Summary of Changes

Date of change:	Version History:	Updated	Description of change:
April 4, 2022	V1 to V2	Added	Environmental Data
April 11, 2022	V2 to V3	Added	Reference for USB ports
May 13, 2022	V3 to V4	Updated	Battery Life
June 6, 2022	V4 to V5	Added	RJ-45 disclaimer in overview and ports section; Manageability disclaimer
July 20, 2022	V5 to V6	Added	Input value in Power section
August 25, 2022	V6 to V7	Updated	Energy Star disclaimer in System Unit section
October 19, 2022	V7 to V8	Updated	Bluetooth version
November 4, 2022	V8 to V9	Updated	HDMI port
December 7, 2022	V9 to V10	Updated	Windows OS
December 19, 2022	V10 to V11	Updated	Battery Life section
January 20, 2023	V11 to V12	Updated	Operating System
March 2, 2023	V12 to V13	Updated	Networking and Communications section
May 18, 2023	V13 to V14	Updated	Storage and Drives section
	V14 to V15		

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Celeron, Pentium, Thunderbolt, Iris and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. AMD and Radeon are trademarks of Advanced Micro Devices, Inc. NVIDIA, the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. SDXC is a registered trademark of SD-3C in the United States, other countries or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. © 2021 Google LLC All rights reserved. Google and the Google Logo are registered trademarks of Google LLC. All other trademarks are the property of their respective owners.